



**ED** 1/2 - 2 Ton  
 Extended Duty Hoist  
 For Special Applications

- Standard lift is 10 feet.
- Totally enclosed, fan-cooled motor for extended operation.
- Highly adaptable for automated plating, heat treating, steel warehouse, foundry, and machine shop use.



**EC** 1/4 - 4 Ton  
 Turnover Hoist  
 For Special Applications

- Standard lift is 15 feet.
- Heavy-duty, specially modified electric chain hoist with two load hooks.
- Completely inverts virtually any shape load with use of simple slings and successively repositioned load hooks.



**MT** 1/4 - 5 Ton  
 Motorized Trolley

- Trolley sideplates feature heavy duty bumpers to act as safety lugs and to protect wheels.
- Available to fit wide-flange and patented track beams.
- Single and two-speed motorized models.



**CYA** 4 - 25 Ton  
 Plain & Geared Trolleys

- For rugged, heavy duty service.
- Available to fit wide-flange and patented track beams.
- Equipped with eight sealed Timken tapered roller bearings and grease fittings.



**CBT** 1/4 - 5 Ton  
 Plain & Geared Trolleys

- Designed to provide superior performance and long, efficient service.
- Wrap-around side plates act as safety lugs and protect wheels.
- Dual tread wheels fit tapered or flat beam flange within range of adjustment. Wheels include permanently lubricated, shielded ball bearings.



**CTA** 1/4 - 5 Ton  
 Plain & Geared Trolleys

- Designed for easy operation with minimal effort.
- Wrap-around side plates act as safety lugs and protect wheels.
- Spark and corrosion resistant wheels available. Track clamps available on 1/4 to 4 ton models.

**VT-A** 1/4 - 5 Ton  
 Push Type Trolley

- Quick set-up with unique dial fit adjusting collar.
- Fits American Standard beams, wide-flange and patented track beams.
- Hardened wheels and stamped steel side plates.
- Negotiates small radius curves.



**BC** 1 - 10 Ton  
 Beam Clamp

- Special clamp jaw design reduces flange stress by distributing load away from flange edge.
- Built-in suspension bar provides lower headroom.



**Customize**  
 with **Coffing**<sup>®</sup>

- Bridge Crane Kits
- Jib Cranes
- LodeRail™ Systems
- Chain Containers
- Cord Reels
- Festooning Packages
- Bronze Wheels / Hooks
- Zinc Plated Chain / Hooks
- Variable Speed Control
- Stainless Steel Chain
- NEMA Push Button Stations
- Infrared Remote Control



104 John James Audubon Parkway  
 Amherst, NY 14228

Phone: (800) 888-0985 • (716) 689-5400  
 Fax: (716) 689-5644 • [www.cmworks.com](http://www.cmworks.com)

In Canada:

Phone: (877) 264-6478 • Fax: (877) 264-6477

**WARNING**

Overloading and Improper Use Can Result In Injury

- To Avoid Injury:
- Do not exceed working load limit, load rating, or capacity.
  - Do not use to lift people or loads over people.
  - Use only alloy chain and attachments for overhead lifting.
  - Read and follow all instructions.

APPLICABLE APPLICATION HOISTS // MOTORIZED TROLLEYS // MANUAL TROLLEYS // ELECTRIC CHAIN HOISTS // ELECTRIC WIRE ROPE HOISTS // AIR CHAIN HOISTS // AIR WIRE ROPE HOISTS // HAND CHAIN HOISTS



**EC** 1/4 - 5 Ton  
Electric Chain Hoist

- Standard lifts are 10, 15, and 20 feet.
- Hook, lug, plain, geared, and motorized trolley suspensions.
- 5-pocket load sheave improves chain support and reduces wear.
- Overload limiting clutch guards against lifting of damaging overloads.
- Adjustable upper and lower limit switches prevent overtravel.
- Dual-braking system - motor and load brakes.



**JLC** 1/8 - 2 Ton  
Electric Chain Hoist

- Standard lifts are 10, 15, and 20 feet.
- Hook, lug, plain, geared, and motorized trolley suspensions.
- Oil bath transmission - gears run longer, quieter.
- Overload limiting clutch guards against lifting of damaging overloads.
- Adjustable upper and lower limit switches prevent overtravel.
- H4 duty cycle. Rated for commercial & industrial applications.



**SLA** 250 - 1000 lb.  
Air Powered Hoist

- Standard lift is 10 feet.
- Heavy-duty, lightweight, compact design. Great for commercial and industrial applications.
- Standard protector overload device.
- 10-pocket oblique lay liftwheel provides longer chain life.
- Variable flow, two lever pendant for precise load spotting.
- Industrial duty air motor for tough applications.



**SLC** 250 - 1000 lb.  
Electric Chain Hoist

- Standard lift is 10 feet.
- Hook suspension.
- H4 duty cycle.
- Very compact and light weight.
- Standard protector overload device.
- Thermally protected hoist duty motor.
- Epoxy powder coat finish.
- Job proven - industrial and commercial applications.



**WR** 1/2 - 5 Ton  
Wire Rope Hoist

- Standard lifts to 70 feet.
- Select single or double reeved and low headroom models.
- Adjustable upper and lower limit switches prevent overtravel.
- Oil-filled transmission runs cooler and lasts longer.
- Adjustable lug mount, plain, geared & motorized trolley suspensions.



**TMM-140A**  
140 kg. / 300 lb.  
Air Manipulator

- Rotary vane motor provides high, uniform torque for quick response and smooth, quiet operation.
- Self-winding, galvanized wire stores internally.
- Handle-mounted pendant control provides one-handed operation.
- Disc brake secures load.



**LHH** 1/2 - 50 Ton  
Hand Chain Hoist

- Standard lifts are 10, 15, and 20 feet.
- Compact and lightweight size allows easy installation and portability.
- Bearing-mounted pinions increase efficiency and ease of operation.
- Through hardened load chain for added strength and wear resistance.
- Economical yet durable.



**EMC EMW** 300 - 500 lb.  
Electric Chain / Wire Rope

- Standard lift is 10 feet.
- Swivel top and bottom hooks w/ safety latches standard.
- Grounded 3-prong plug - easy installation in any std. 115V outlet.
- Compact design
- Upper and lower limit switches.
- Thermal motor protection.
- Light duty operation.



**CAH** 1/2 - 3 Ton\*  
Air Powered Hoist

- Standard lift is 10 feet.
- Aluminum housing provides strength and portability.
- 8-vane rotary motor provides high, uniform torque for quick response and smooth, quiet operation.
- Several suspension options available including motorized trolley.
- Spark resistant models.

\* 1/4 - 1 Ton - small frame models



**LSB-B** 3/4 - 6 Ton  
Ratchet Lever Hoist

- Standard lifts are 5, 10, 15, and 20 feet.
- Low handle effort.
- Short 360° rotating handle assures precise positioning.
- Optional load limiter available.
- Easy to free chain.
- Steel housing.



**TB-602** 550 lb.  
**TB-603** 1100 lb.  
Ratchet Lever Hoists

- 5 ft. and 10 ft. lifts available.
- Hardend link-type steel load chain and Weston-type load brake are standard.
- Lightweight and compact. Easy tool box storage.
- Impact resistant.



**PA** 3/4 - 3 Ton  
Ratchet Lever Hoist

- Standard lifts are 5, 10, 15, and 20 feet.
- Easy to free chain.
- Short handle with low handle effort.
- Link chain.
- Aluminum housing.



**RA** 3/4 - 6 Ton  
Ratchet Lever Hoist

- Standard lift is 5 feet.
- Dual ratchet and pawl design provides easy operation.
- Link chain.
- Aluminum housing.
- Multiple rigging options.



**G Model** 3/4 - 15 Ton  
Ratchet Lever Hoist

- Standard lift is 5 feet.
- Single or double-locking pawl models available.
- Can be used to lift or pull.
- Easy operation from either side.
- Roller chain.
- Malleable iron housing.



**Cable Hoists** 1/4 - 2 Ton  
Ratchet Lever Hoists

- Single and double line.
- Lift heights to 29 feet.
- Reversible handle bends when overloaded.
- Lightweight and rugged.
- 4:1 safety factor meets ANSI Standard B-30.21.

Longer Lifts Available On Most Hoists - Please Call For More Information

Coffing Hoists Feature A Lifetime Warranty On All Products