

ResinDek<sup>®</sup> Xspan<sup>®</sup> is a 1 1/8" thick panel that offers the look, maintainability and performance of ResinDek<sup>®</sup> in a structural flooring solution where a corrugated metal substructure is not required in certain applications.

- Extensively tested and capable of safely supporting 125 psf dead loads at 32" center supports and 2,300 lbs pallet jack loads without corrugated metal B deck. Please refer to the table below for ResinDek<sup>®</sup> Loads and Spans for allowable point loads, uniform loads and pallet jack live and dead loads.
- Available in Gray Diamond Seal 2<sup>™</sup> and ESD finishes
- Comes with standard high gloss white underside to enhance lighting
- Variety of lengths, widths and tongue and groove configurations offered to fit custom aisles and storage rack applications

**ResinDek<sup>®</sup> Xspan flooring panels have been approved by IBC Code Officials for use as a structural flooring system in certain applications.** Structural supports must be reviewed and approved by Cornerstone Specialty Wood Products and must be capable of supporting the floor loads at the specified intervals. **For further details, check with Cornerstone Specialty Wood Products and/or your local building code officials.**



**ResinDek<sup>®</sup> Xspan<sup>®</sup> Load Span Tables**

Type of Load	Unit of Measure	Span (inch / Allowable Load)			
		16	24	32	40
Hand Pallet Truck Loads:	Lbs	3,000	2,700	2,300	2,000
Uniform Loads:	Lbs/Ft <sup>2</sup>	375	225	125	75
Point Loads on Plates:					
Plate Size (inch)					
2 x 2	Lbs	676	616	540	317
3 x 3	Lbs	737	646	575	350
4 x 4	Lbs	785	686	620	365
5 x 5	Lbs	820	705	635	384
6 x 6	Lbs	935	806	700	402



[www.resindek.com](http://www.resindek.com)