

HEAVY DUTY VALUE SERIES

STANDARD FEATURES

- Heat treat hardened and factory lubricated swivel raceways with an upper raceway zerk grease fitting.
- Casters have 1/4" top plate and welded leg construction with a clear zinc chromate finish.
- Casters have 1/2" nut and bolt axle with a zerk grease fitting and a roller bearing wheel.
- Options: side cam brake, over-the-wheel strap brake, trailing end brake, total-lock brake, field installed bolt-on 4-position swivel lock - 8G000308497

Economical Heavy Duty Caster Series that are zinc plated and have one plate option only. Full compliment of wheel options available. Check with factory for options.

Options: Side Cam Brake, Over-The-Wheel Strap Brake, Trailing End Brake, Total-Lock Brake, field installed bolt-on 4-Position Swivel Lock - 8G000308497

Applications: Trucks & Hoppers, Carts & Dollies, Racks, and other various mobile equipment



**Driven
to Exceed
Expectations**

800-558-0117

www.erwagner.com

Caster Specifications


A Wheel Dia. (inches)	Approximate Tread Width (inches)	Caster Capacity (pounds)	Wheel Bearing Type	B Height (inches)	C Swivel Radius (inches)	Approximate Weight (pounds)†	Swivel Caster Part No.	Rigid Caster Part No.
MOLD-ON RUBBER SOFT TREAD WHEEL/ALUMINUM HUB (Aluminum Hub/Black Tread)								
4	2	300	Roller	5-5/8	3-7/16	5-3/4	8W8804514000190	8W8304514000190
5	2	350	Roller	6-1/2	4-1/8	6-1/4	8W8805514000190	8W8305514000190
6	2	410	Roller	7-1/2	4-7/8	6-3/4	8W8806514000190	8W8306514000190
8	2	500	Roller	9-1/2	6-3/16	8-1/4	8W8808514000190	8W8308514000190
POLY II RUBBER SOFT TREAD WHEEL/POLYOLEFIN HUB (Gray Hub/Black Tread)								
4	2	300	Roller	5-5/8	3-7/16	5	8W8804C26000190	8W8304C26000190
5	2	325	Roller	6-1/2	4-1/8	5-3/4	8W8805C26000190	8W8305C26000190
6	2	400	Roller	7-1/2	4-7/8	6-1/4	8W8806C26000190	8W8306C26000190
8	2	475	Roller	9-1/2	6-3/16	7-1/2	8W8808C26000190	8W8308C26000190
TPR RUBBER SOFT DONUT TREAD WHEEL/POLYOLEFIN HUB (Gray Hub/Gray Tread)								
5	2	325	Roller	6-1/2	4-1/8	5-3/4	8W8805C55000190	8W8305C55000190
6	2	450	Roller	7-1/2	4-7/8	6-1/4	8W8806C55000190	8W8306C55000190
8	2	500	Roller	9-1/2	6-3/16	7-1/2	8W8808C55000190	8W8308C55000190
POLY II POLY HARD TREAD WHEEL (All Black)								
4	2	400	Roller	5-5/8	3-7/16	5	8W8804C27000190	8W8304C27000190
5	2	650	Roller	6-1/2	4-1/8	5-3/4	8W8805C27000190	8W8305C27000190
6	2	700	Roller	7-1/2	4-7/8	6-1/4	8W8806C27000190	8W8306C27000190
8	2	900	Roller	9-1/2	6-3/16	6-3/4	8W8808C27000190	8W8308C27000190
POLY II URETHANE SOFT TREAD WHEEL/POLYOLEFIN HUB (Gray Hub/Red Tread)								
4	2	600	Roller	5-5/8	3-7/16	5	8W8804C25000190	8W8304C25000190
5	2	750	Roller	6-1/2	4-1/8	5-3/4	8W8805C25000190	8W8305C25000190
6	2	900	Roller	7-1/2	4-7/8	6-1/4	8W8806C25000190	8W8306C25000190
8	2	900	Roller	9-1/2	6-3/16	7-1/2	8W8808C25000190	8W8308C25000190
MOLD-ON POLYURETHANE SOFT TREAD WHEEL/ALUMINUM HUB (Aluminum Hub/Red Tread)								
4	2	700	Roller	5-5/8	3-7/16	5-3/4	8W8804525000190	8W8304525000190
5	2	1050	Roller	6-1/2	4-1/8	7-1/2	8W8805525000190	8W8305525000190
6	2	1200	Roller	7-1/2	4-7/8	8	8W8806525000190	8W8306525000190
8	2	1200	Roller	9-1/2	6-3/16	8-3/4	8W8808525000190	8W8308525000190
DURATEX HARD TREAD WHEEL (All Black)								
4	2	800	Roller	5-5/8	3-7/16	5-3/4	8W8804438000190	8W8304438000190
5	2	1000	Roller	6-1/2	4-1/8	6	8W8805438000190	8W8305438000190
6	2	1200	Roller	7-1/2	4-7/8	7	8W8806438000190	8W8306438000190
8	2	1200	Roller	9-1/2	6-3/16	9	8W8808438000190	8W8308438000190
SEMI-STEEL HARD TREAD WHEEL (All Black)								
4	2	1000	Roller	5-5/8	3-7/16	9	8W8804411000190	8W8304411000190
5	2	1000	Roller	6-1/2	4-1/8	9-1/2	8W8805411000190	8W8305411000190
6	2	1200	Roller	7-1/2	4-7/8	10	8W8806411000190	8W8306411000190
8	2	1200	Roller	9-1/2	6-3/16	14	8W8808411000190	8W8308411000190

† Weight is standard swivel. (Rigid is lighter.)



90 Top Plate

Overall Size: 4" x 4-1/2"
Hole Spacing: 2-5/8" x 3-5/8" slotted to 3" x 3"
Hole Diameter: 3/8" x 3/4" slots
Bolt Diameter: 3/8"



**Driven
to Exceed
Expectations**
800-558-0117
www.erwagner.com