

LIGHT DUTY SWIVEL AND RIGID CASTERS

STANDARD FEATURES

- Double row swivel construction
- Heat treat hardened and factory lubricated swivel raceways
- Zinc-plated finish for corrosion resistance and appearance
- 5/16" diameter axle

Ideal for light duty industrial and healthcare applications, office and retail light duty carts, dollies, stands, hampers, cabinets, racks, and other light duty mobile equipment.

Options: Pinch Brake, Strap Brake, Trailing End Brake, Thread Guards, NSF Certification, Rivet Axle.



**Driven
to Exceed
Expectations**

800-558-0117

www.erwagner.com

Caster Specifications

A	Approximate	Caster	Wheel	B	C	Approximate	Swivel	Rigid	Swivel
Wheel Dia. (inches)	Tread Width (inches)	Capacity (pounds)	Bearing Type	Height (inches)	Swivel Radius (inches)	Weight (pounds)	Plate Caster Part No.	Plate Caster Part No.	Stem Caster Part No.*
Cushionex Supreme - Soft Rubber Tread / Hard Rubber Hub Wheel (All black)									
3	1	100	Delrin	3-13/16	2-3/4	1-1/4	2F68030040001**	1F63030040001**	2F69030040001**
4	1	115	Delrin	4-13/16	3-1/4	1-1/2	2F68040040001**	1F63040040001**	2F69040040001**
5	1	125	Delrin	5-13/16	4	2	2F68050040001**	1F63050040001**	2F69050040001**
Poly II Rubber - Thermoplastic Rubber Tread/Polyolefin Hub Wheel (Gray Tread / Gray Hub)									
3	1	125	Plain	3-13/16	2-3/4	1	2F6803P260001**	1F6303P260001**	2F6903P260001**
4	1	135	Plain	4-13/16	3-1/4	1-1/4	2F6804P260001**	1F6304P260001**	2F6904P260001**
5	1	145	Plain	5-13/16	4	1-1/2	2F6805P260001**	1F6305P260001**	2F6905P260001**
Spartan Supreme - All Hard Rubber Wheel (All Black)									
3	1	125	Delrin	3-13/16	2-3/4	1-1/4	2F68030090001**	1F63030090001**	2F69030090001**
4	1	140	Delrin	4-13/16	3-1/4	1-1/2	2F68040090001**	1F63040090001**	2F69040090001**
5	1	145	Delrin	5-13/16	4	2	2F68050090001**	1F63050090001**	2F69050090001**
Durafoam - Polyolefin Wheel (All Black)									
3	1	125	Plain	3-13/16	2-3/4	1	2F68030270001**	1F63030270001**	2F69030270001**
4	1	140	Plain	4-13/16	3-1/4	1-1/4	2F68040270001**	1F63040270001**	2F69040270001**
5	1	145	Plain	5-13/16	4	1-1/2	2F68050270001**	1F63050270001**	2F69050270001**
Poly II Urethane - Polyurethane Tread/Polyolefin Hub Wheel (Blue Tread / Gray Hub)									
3	1	125	Plain	3-13/16	2-3/4	1	2F6803P250001**	1F6303P250001**	2F6903P250001**
4	1	140	Plain	4-13/16	3-1/4	1-1/4	2F6804P250001**	1F6304P250001**	2F6904P250001**
5	1	145	Plain	5-13/16	4	1-1/2	2F6805P250001**	1F6305P250001**	2F6905P250001**

(*) Stem casters are 1/8" shorter than plate casters.

**** Plate Code Number**



Overall Size 2-3/4" x 3-3/4"
Hole Spacing 1-3/4" x 3"
Hole Diameter 11/32"
Bolt Diameter 5/16"




Overall Size 3-1/8" x 4-1/8"
Hole Spacing 1-3/4" x 3" to 2-3/8" x 3-3/8"
Hole Diameter 3/8" x 3/4" slots
Bolt Diameter 5/16"



Overall Size 2-3/4" x 3-3/4"
Hole Spacing 1-3/4" x 2-5/8" to 3"
Hole Diameter 11/32" x 1/2" slots
Bolt Diameter 5/16"



Overall Size 3-1/8" x 4-1/8"
Hole Spacing 2-3/8" x 3-7/16"
Hole Diameter 11/32"
Bolt Diameter 5/16"



Overall Size 3-3/4" x 4-5/8"
Hole Spacing 2-5/8" x 3-5/8" to 3" x 3"
Hole Diameter 3/8" x 3/4" slots
Bolt Diameter 5/16"

**** Plate Code Number**

Stem Choices

Friction Ring Stems




Stem Size Dia. x Length (D) (L)	**Stem Code Number
7/16 x 1-3/8	01
7/16 x 1-29/32	03
5/8 x 2-3/16	ZW
13/16 x 1-3/4	37



Threaded Stems

Stem Size Dia. x TPI x Length (D) (TPI) (L)	**Stem Code Number
3/8 - 16 x 1	04
3/8 - 16 x 1-1/2	07
7/16 - 14 x 7/8	23
7/16 - 14 x 1-1/2	05
1/2 - 13 x 3/4	06
1/2 - 13 x 1	61
1/2 - 13 x 1-1/2	10
Expandable	25



Octagon Stems

Stem Size Dia. x Length (D) (L)	Hole Size	Hole Location (A)	Hole Location (E)	**Stem Code Number
.750 x 2	3 @ .265"	1"	.375"	74
.860 x 2	1 @ .265"	1"	—	36

Other stem and plate sizes available upon request.

Driven to Exceed Expectations
800-558-0117

www.erwagner.com

Brake Options

