

MEDIUM DUTY CASTER SERIES

STANDARD FEATURES

- Double row swivel construction.
- 3/8" diameter nut and bolt axle.
- Zinc-plated finish for corrosion resistance and appearance.
- Heat treat hardened and factory lubricated swivel raceways.
- Assembly wrench for threaded stem swivel casters: 8G000192797

All purpose casters that are good for all applications with load ratings of 200 - 400 lbs. Both plate and stem mounting options.

Options: Side Pinch Brake, Thread Guards, Roller Wheel Bearings, Ball Wheel Bearings, NSF Certification, Nickel Plated Finish, Rivet Axle.

Applications: Medium Duty Office Applications, Dollies, Hand Carts, Cabinets, Racks, and General Purpose Industrial and Commercial.



**Driven
to Exceed
Expectations**

800-558-0117

www.erwagner.com

Caster Specifications

A Wheel Dia. (inches)	Approximate Tread Width (inches)	Caster Capacity (pounds)	Wheel Bearing Type	B Height (inches)*	C Swivel Radius (inches)	Approximate Weight (pounds)	Swivel Plate Caster Part No.	Rigid Plate Caster Part No.	Swivel Stem Caster Part No.
CUSHIONEX SUPREME WHEEL									
4	1-3/8	200	Delrin	5-1/16	3-3/8	2-1/2	1F28040040001**	1F23040040001**	1F29040040001**
5	1-3/8	240	Delrin	6-1/16	3-15/16	3	1F28050040001**	1F23050040001**	1F29050040001**
6	1-3/8	280	Delrin	7-1/16	4-15/16	4	1F28060040001**	1F23060040001**	1F29060040001**
POLY II RUBBER WHEEL									
4	1-1/2	275	Delrin	5-1/16	3-3/8	2	1F2804B260001**	1F2304B260001**	1F2904B260001**
5	1-1/2	300	Delrin	6-1/16	3-15/16	2-1/4	1F2805B260001**	1F2305B260001**	1F2905B260001**
6	1-1/2	300	Delrin	7-1/16	4-15/16	2-1/2	1F2806B260001**	1F2306B260001**	1F2906B260001**
SPARTAN SUPREME WHEEL									
4	1-3/8	300	Delrin	5-1/16	3-3/8	2-1/2	1F28040090001**	1F23040090001**	1F29040090001**
5	1-3/8	350	Delrin	6-1/16	3-15/16	3	1F28050090001**	1F23050090001**	1F29050090001**
6	1-3/8	400	Delrin	7-1/16	4-15/16	4	1F28060090001**	1F23060090001**	1F29060090001**
DURAFOAM WHEEL									
4	1-3/8	300	Plain	5-1/16	3-3/8	2	1F28040270001**	1F23040270001**	1F29040270001**
5	1-3/8	350	Plain	6-1/16	3-15/16	2-1/4	1F28050270001**	1F23050270001**	1F29050270001**
6	1-3/8	400	Plain	7-1/16	4-15/16	2-3/4	1F28060270001**	1F23060270001**	1F29060270001**
POLY II POLY WHEEL									
4	1-3/8	375	Delrin	5-1/16	3-3/8	2	1F2804B270001**	1F2304B270001**	1F2904B270001**
5	1-3/8	400	Delrin	6-1/16	3-15/16	2-1/4	1F2805B270001**	1F2305B270001**	1F2905B270001**
6	1-3/8	400	Delrin	7-1/16	4-15/16	2-1/2	1F2806B270001**	1F2306B270001**	1F2906B270001**
POLY II URETHANE WHEEL									
4	1-1/2	375	Delrin	5-1/16	3-3/8	2	1F2804B250001**	1F2304B250001**	1F2904B250001**
5	1-1/2	400	Delrin	6-1/16	3-15/16	2-1/4	1F2805B250001**	1F2305B250001**	1F2905B250001**
6	1-1/2	400	Delrin	7-1/16	4-15/16	2-1/2	1F2806B250001**	1F2306B250001**	1F2906B250001**

** NOTE: For your plate choice, replace ** in part number with plate code number shown in top plate choices.
(*) Stem casters are 3/16" shorter than plate casters.

** Plate Code Number

Mounting Choices



Overall Size: 2-3/4" x 3-3/4"
Hole Spacing: 1-3/4" x 3"
Hole Diameter: 11/32"
Bolt Diameter: 5/16"



Overall Size: 3-1/8" x 4-1/8"
Hole Spacing: 2-3/8" x 3-7/16"
Hole Diameter: 11/32"
Bolt Diameter: 5/16"



Overall Size: 3-1/8" x 4-1/8"
Hole Spacing: 1-3/4" x 3" to 2-3/8" x 3-3/8"
Hole Diameter: 3/8" x 3/4" slots
Bolt Diameter: 5/16"



Overall Size: 3-3/4" x 4-5/8"
Hole Spacing: 2-5/8" x 3-5/8" to 3" x 3"
Hole Diameter: 3/8" x 3/4" slots
Bolt Diameter: 5/16"



Friction Ring Stems



Stem Size Dia. x Length (D) x (L)	** Stem Code Number
7/16 x 1-29/32	03
13/16 x 1-3/4	37
1 x 2-1/2	ZX

Threaded Stems



Stem Size Dia. - TPI x (D) (TPI)	Length (L)	** Stem Code Number
1/2- 13 x	3/4	06
1/2- 13 x	1	61
1/2- 13 x	1-1/2	10
5/8- 18 x	1-1/2	45
3/4- 10 x	1-1/2	ZT
1/2- 13 x	2-1/2	25

(expandable)

Octagon Stems



Stem Size Dia. x Length (D) x (L)	Hole Size	Hole Location (A)	Hole Location (E)	** Stem Code Number
.750 x 2	3 @ .265"	1"	.375"	74
.860 x 2	1 @ .265"	1"	-	36

(Other stem sizes and plate sizes available on request)

**Driven
to Exceed
Expectations**

800-558-0117

www.erwagner.com