

FOAM FILLED WHEEL CASTERS

STANDARD FEATURES

- Double row swivel construction with extra large raceways for long service life.
- Heat treat hardened and factory lubricated swivel raceways with swivel grease fitting (Not 6”).
- Foam filled wheel gives a cushioned ride to protect delicate loads. Provides very quiet operation and superior protection for floors. Tires won't go flat.

Foam filled wheel casters are designed to absorb the shock and vibration caused by the imperfections in the floor and uneven terrain just like pneumatic wheel casters. The difference is that these wheels never need to be filled with air. The purpose of these casters is to deliver a smooth and safe ride for delicate loads. These casters are not designed for towing applications.

Applications: Light to medium capacity carts, racks, hospitals, scientific and electronic laboratories, hotels, department stores and TV or movie studios.



**Driven
to Exceed
Expectations**

800-558-0117

www.erwagner.com

Caster Specifications

A Wheel Dia. (inches)	Approximate Tread Width (inches)	Caster Capacity (pounds)	Wheel Bearing Type	B Height (inches)	C Swivel Radius* (inches)	Approximate Weight (pounds)†	Swivel Caster Part No.	Swivel w/Brake Part No. Total-Lock (6") Strap Brake (8")	Rigid Caster Part No.
FOAM FILLED SOFT TREAD WHEEL/STEEL HUB (SILVER HUB/GRAY TREAD)									
6	2	200	Ball	7-1/2	5-1/2	4-1/2	4FN8062610001AR	4FN8062610071AR	4FN3062610001AR
6	2	200	Ball	7-1/2	5-1/2	5	4FN806261000190	4FN806261007190	4FN306261000190
8	2.80/2.50-4	300	Ball	9-11/16	6-1/2	7	8FN808261000190	8FN808261005190	8FN308261000190
10	4.10/3.10-4	350	Ball	11-13/16	7-5/8	7-1/2	8FN80T261000190	N/A	8FN30T261000190
FOAM FILLED SOFT TREAD WHEEL/STEEL HUB (SILVER HUB/BLACK TREAD)									
6	2	200	Ball	7-1/2	5-1/2	4-1/2	4FN8062710001AR	4FN8062710071AR	4FN3062710001AR
6	2	200	Ball	7-1/2	5-1/2	5	4FN806271000190	4FN806271007190	4FN306271000190
8	2.80/2.50-4	300	Ball	9-11/16	6-1/2	7	8FN808271000190	8FN808271005190	8FN308271000190
10	4.10/3.10-4	350	Ball	11-13/16	7-5/8	7-1/2	8FN80T271000190	N/A	8FN30T271000190

(*) Swivel Radius on the 6" represents a swivel caster with Total-Lock Brake (Non Brake versions will be less).

† Weight represents a swivel caster (Brake version will be 1/2 lb. more and Rigid will be 1/2 lb. less).




Top Plate Choices

AR Plate Dimensions



Overall Size: 2-3/4" x 3-3/4"
Hole Spacing: 1-3/4" x 2-7/8" to 3"
Hole Diameter: 11/32" x 13/32" slots
Bolt Diameter: 5/16"

90 Plate Dimensions



Overall Size: 4" x 4-1/2"
Hole Spacing: 2-5/8" x 3-5/8" to 3" x 3"
Hole Diameter: 3/8" x 3/4" slots
Bolt Diameter: 3/8"

**Driven
to Exceed
Expectations**

800-558-0117

www.erwagner.com