

MEDIUM DUTY STAINLESS STEEL CASTERS

STANDARD FEATURES

- Stainless steel wheel spanners, greaseable axle and locknut
- Grease zerk fittings in upper raceway for easy maintenance
- Stainless steel mounting plates
- High temperature wheel rated to 550° F intermittent

Stainless steel components are impervious to cleaning agents, steam, and corrosives. Dust cover with grease zerk fitting provides easy maintenance. All casters(except high-temperature) have upper and lower grease seals. High heat will melt grease seals. All casters have nonmarking wheels and self-lubricating wheel bearings. Optional strap brakes available.



Bussing Cart



Stainless Steel Utility Cart



Food Service Cart

**Driven
to Exceed
Expectations**

800-558-0117

www.erwagner.com

Caster Specifications

A Wheel Dia. (inches)	Approximate Tread Width (inches)	Caster Capacity (pounds)	Wheel Bearing Type	B Height (inches)	C Swivel Radius (inches)	Approximate Weight (pounds)	Swivel Plate Caster Part No.	Rigid Plate Caster Part No.	Swivel Stem Caster Part No.
TPR SOFT RUBBER FLAT TREAD (GRAY TREAD / LIGHT GRAY HUB)									
3	1-1/4	200	Delrin	4-1/16	3	1-1/4	7F08A3B52080FAM	7F0343B52050FAM	7F09A3B52080F**
3-1/2	1-1/4	250	Delrin	4-9/16	3-1/4	2	7F08A9B52080FAM	7F0349B52050FAM	7F09A9B52080F**
4	1-1/4	275	Delrin	5-1/16	3-1/2	2-1/4	7F08A4B52080FAM	7F0344B52050FAM	7F09A4B52080F**
5	1-1/4	300	Delrin	6-3/16	4	2-3/4	7F08A5B52080FAM	7F0345B52050FAM	7F09A5B52080F**
TPR SOFT RUBBER DONUT TREAD (GRAY TREAD / LIGHT GRAY HUB)									
3	1-1/4	200	Delrin	4-1/16	3	1-1/4	7F08A3B55080FAM	7F0343B55050FAM	7F09A3B55080F**
3-1/2	1-1/4	225	Delrin	4-9/16	3-1/4	2	7F08A9B55080FAM	7F0349B55050FAM	7F09A9B55080F**
4	1-1/4	250	Delrin	5-1/16	3-1/2	2-1/4	7F08A4B55080FAM	7F0344B55050FAM	7F09A4B55080F**
5	1-1/4	250	Delrin	6-3/16	4	2-3/4	7F08A5B55080FAM	7F0345B55050FAM	7F09A5B55080F**
6	1-1/4	300	Delrin	7-3/16	4-1/2	3-1/4	7F08A6B55080FAM	7F0346B55050FAM	7F09A6B55080F**
POLYURETHANE FLAT TREAD (GRAY TREAD / LIGHT GRAY HUB)									
3	1-1/4	200	Delrin	4-1/16	3	1-1/4	7F08A3B56080FAM	7F0343B56050FAM	7F09A3B56080F**
3-1/2	1-1/4	250	Delrin	4-9/16	3-1/4	2	7F08A9B56080FAM	7F0349B56050FAM	7F09A9B56080F**
4	1-1/4	275	Delrin	5-1/16	3-1/2	2-1/4	7F08A4B56080FAM	7F0344B56050FAM	7F09A4B56080F**
5	1-1/4	300	Delrin	6-3/16	4	2-3/4	7F08A5B56080FAM	7F0345B56050FAM	7F09A5B56080F**
6	1-1/4	300	Delrin	7-3/16	4-1/2	3-1/4	7F08A6B56080FAM	7F0346B56050FAM	7F09A6B56080F**
POLYOLEFIN FLAT TREAD (ALL BLACK)									
3	1-1/4	200	Plain	4-1/16	3	1-1/4	7F08A3127080FAM	7F0343127050FAM	7F09A3127080F**
3-1/2	1-1/4	250	Plain	4-9/16	3-1/4	2	7F08A9127080FAM	7F0349127050FAM	7F09A9127080F**
4	1-1/4	275	Plain	5-1/16	3-1/2	2-1/4	7F08A4127080FAM	7F0344127050FAM	7F09A4127080F**
5	1-1/4	300	Plain	6-3/16	4	2-3/4	7F08A5127080FAM	7F0345127050FAM	7F09A5127080F**
HIGH TEMPERATURE NYLON GLASS FILLED (ALL BLACK)									
3	1-1/4	200	Plain	4-1/16	3	1-1/4	7F08B3044080FAM	7F0343044050FAM	7F09B3044080F**
3-1/2	1-1/4	250	Plain	4-9/16	3-1/4	2	7F08B9044080FAM	7F0349044050FAM	7F09B9044080F**
4	1-1/4	275	Plain	5-1/16	3-1/2	2-1/4	7F08B4044080FAM	7F0344044050FAM	7F09B4044080F**
5	1-1/4	300	Plain	6-3/16	4	2-3/4	7F08B5044080FAM	7F0345044050FAM	7F09B5044080F**

** NOTE: For your stem choice, replace ** in part number with plate or stem code number shown in stem choices.
Swivel stem caster heights are 1/8" shorter than heights listed. Rigid casters are 1/2 pound lighter than listed.

Mounting Plates

Swivel Plate




Overall Size: 2-3/8" x 3-5/8"
Hole Spacing: 1-3/4" x 2-11/16"
slotted to 3"
Bolt Diameter: 5/16"

Rigid Plate



Overall Size: 2-5/8" x 3-5/8"
Hole Spacing: 1-3/4" x 2-11/16"
slotted to 3"
Bolt Diameter: 5/16"



Stem Choices

Friction Ring Stems



Stem Size Dia. x Length (D) x (L)	** Stem Code Number
0.845 x 2-3/16 (round)	73

Threaded Stems

Stem Size Dia. -TPI x Length (D) (L)	** Stem Code Number
1/2- 13 x 1-1/2	10
1/2- 13 x 2-3/4 (expandable)	20



Medium Duty Adapters



** Stem Code Number	Fits Tubing I.D. Size
E5	0.852" to 0.927"
E9	1.030" to 1.140"
E7	1.178" to 1.303"
E6	1.426" to 1.589"

**Driven
to Exceed
Expectations
800-558-0117**

www.erwagner.com