

PNEUMATIC WHEEL CASTERS

STANDARD FEATURES

- Double row swivel construction with extra large raceways for long service life.
- Heat treat hardened and factory lubricated swivel raceways with swivel grease fitting (Not 6”).
- Full pneumatic wheel gives a cushioned ride to protect delicate loads. Provides very quiet operation and superior protection for floors.

Pneumatic wheel casters are designed to absorb the shock and vibration caused by the imperfections of the floor and uneven terrain. The purpose of these casters is to deliver a smooth and safe ride for delicate loads when harder surfaced wheels won't handle the task. These casters are not designed for towing applications.

Applications: Light to medium capacity carts, racks, hospitals, scientific and electronic laboratories, hotels, department stores and TV or movie studios.



**Driven
to Exceed
Expectations**

800-558-0117

www.erwagner.com

Product Specifications

A	Approximate Wheel Dia. (inches)	Approximate Tread Width (inches)	Caster Capacity (pounds)	Wheel Bearing Type	B	C	Approximate Weight (pounds)†	Swivel Caster Part No.	Swivel w/Brake Part No. Total-Lock (6") Strap Brake (8")	Rigid Caster Part No.
FULLY PNEUMATIC SOFT TREAD WHEEL/STEEL HUB (SILVER HUB/GRAY TREAD)										
	6	2	200	Ball	7-1/2	5-1/2	4-1/2	4FN8062540001AR	4FN8062540071AR	4FN3062540001AR
	6	2	200	Ball	7-1/2	5-1/2	5	4FN806254000190	4FN806254007190	4FN306254000190
	8	2.80/2.50-4	300	Ball	9-11/16	6-1/2	7	8FN808254000190	8FN808254005190	8FN308254000190
	10	4.10/3.10-4	350	Ball	11-13/16	7-5/8	7-1/2	8FN80T254000190	N/A	8FN30T254000190
FULLY PNEUMATIC SOFT TREAD WHEEL/STEEL HUB (SILVER HUB/BLACK TREAD)										
	6	2	200	Ball	7-1/2	5-1/2	4-1/2	4FN8062120001AR	4FN8062120071AR	4FN3062120001AR
	6	2	200	Ball	7-1/2	5-1/2	5	4FN806212000190	4FN806212007190	4FN306212000190
	8	2.80/2.50-4	300	Ball	9-11/16	6-1/2	7	8FN808212000190	8FN808212005190	8FN308212000190
	10	4.10/3.10-4	350	Ball	11-13/16	7-5/8	7-1/2	8FN80T212000190	N/A	8FN30T212000190

(*) Swivel Radius on the 6" represents a swivel caster with Total-Lock Brake (Non Brake versions will be less).

† Weight represents a swivel caster (Brake version will be 1/2 lb. more and Rigid will be 1/2 lb. less).



Top Plate Choices

AR Plate Dimensions



Overall Size: 2-3/4" x 3-3/4"
Hole Spacing: 1-3/4" x 2-7/8" to 3"
Hole Diameter: 11/32" x 13/32" slots
Bolt Diameter: 5/16"

90 Plate Dimensions



Overall Size: 4" x 4-1/2"
Hole Spacing: 2-5/8" x 3-5/8" to 3" x 3"
Hole Diameter: 3/8" x 3/4" slots
Bolt Diameter: 3/8"

Keep Tires Properly Inflated

**Driven
to Exceed
Expectations**

800-558-0117

www.erwagner.com

