

POWDER COATED DRUM DOLLIES

STANDARD FEATURES

- Heavy duty steel construction
- Spotwelded for extra strength
- Gray powder coat enamel finish. Other colors available when ordered in quantities of 25 or more
- The five outriggered casters provide a wider stance and shorter distance between wheels for extra stability
- Center plate mounting holes available for a sixth caster for point load applications on 5-wheel dollies

Drum dollies add mobility to heavy duty industrial drums and enable these drums to be used as containers for scrap metal, liquids, parts, and refuse. 4-wheel dollies have a spotwelded cross braced frame for extra strength. 5-wheel dollies provide better stability and a higher load rating. Chart with dimensions on the back page.



4-Wheel Drum Dolly with 3" x 1 1/4" Polyolefin Wheels



5-Wheel Drum Dolly with 5" x 2" Polyolefin Wheels



5-Wheel Drum Dolly with 3" x 1" Semi-Steel Wheels

**Driven
to Exceed
Expectations**

800-558-0117

www.erwagner.com

SPECIFICATIONS

| Drum Size | Dolly Capacity (Pounds) | Wheel Type | Wheel Size (Inches) | Overall Height (Inches) | Inside Dimension (Inches) | Outside Dimension (Inches) | Dolly Part Number | Caster Pack Part Number |
|--------------------------------|-------------------------|------------|-----------------------------------|-------------------------------|--------------------------------|--------------------------------|-------------------|-------------------------|
| Four Wheel Drum Dollies | | | | | | | | |
| 30 Gal. | 1000 | Polyolefin | 3 x 1 ¹ / ₄ | 6 ¹ / ₂ | 19 ¹ / ₈ | 19 ¹ / ₂ | 2F000249990 | 2F000247894 |
| 55 Gal. | 1000 | Polyolefin | 3 x 1 ¹ / ₄ | 6 ¹ / ₂ | 23 ¹ / ₈ | 23 ¹ / ₂ | 2F000249890 | 2F000247894 |
| 55 Gal. | 1400 | Polyolefin | 3 x 1 ³ / ₄ | 6 ¹ / ₂ | 23 ¹ / ₈ | 23 ¹ / ₂ | 1F000249790 | 1J000247794 |
| Five Wheel Drum Dollies | | | | | | | | |
| 55 Gal. | 1250 | Polyolefin | 3 x 1 ¹ / ₄ | 6 ¹ / ₂ | 23 ¹ / ₈ | 23 ¹ / ₂ | 2F004378690 | 2J000273294 |
| 55 Gal. | 1400 | Semi-Steel | 3 x 1 | 6 ¹ / ₂ | 23 ¹ / ₈ | 23 ¹ / ₂ | 2F004378790 | 2J000270294 |
| 55 Gal. | 1400 | Polyolefin | 5 x 2 | 8 ³ / ₄ | 23 ¹ / ₈ | 23 ¹ / ₂ | 1F004445390 | 1J000364994 |

Center plate mounting holes available to mount a sixth caster for point load applications on 5-wheel dollies.

| | | |
|-------------------------|--------------------------------------|-----------------|
| Polyolefin Wheel Caster | 3" X 1 ¹ / ₄ " | 2F9803027000100 |
| Semi-Steel Wheel Caster | 3" X 1" | 2F9803011000100 |
| Polyolefin Wheel Caster | 5" x 2" | 1F3805027000100 |

Sixth caster mounting holes in the center of the bottom plate.



For ordering, please call your local Rep. or contact the Factory

**Driven
 to Exceed
 Expectations**
800-558-0117
www.erwagner.com