



MT2010A™ **10.1" RUGGED TABLET** – Light and thin, but still rugged

You need a tablet for your field service or warehouse employees that is rugged enough to stand up to the abuse every day and can run the applications and software you are already using? That is where the MT2010A rugged tablet comes in.

The MT2010A withstands a 4-foot drop without a problem and runs full version of Android™ operating system. The large display of the 10.1-inch projected capacitive touchscreen is sunlight-readable so you can work outside as easily as inside. No more squinting at a small, difficult-to-read screen.

Tired of dealing with the repair costs of consumer grade tablets?

The MT2010A is IP65 dustproof and water resistant and will work in temperatures of -20 to +50 °C / -4 to +122 °F.

With light weight and no more than 21 mm / 0.83 inch thick,

the tablet can easily be mounted in any truck or forklift where they can be removed by operators for use on the job.

Key Features

- Cortex-A53 Octa-core processor
- 10.1" 1280 x 720 TFT Panel with direct optical bonding
- Android operating system
- Hot-swappable battery
- IP65 waterproof and dustproof
- Designed for use in extreme temperatures
- Optional integrated 1D/2D barcode reader
- Supports NFC functions
- 8MP rear camera with LED flash and 2MP front camera

Because it Works!™

MT2010A™ Product Specifications

Base unit	
Display	10.1" (1280 x 800 WUXGA)
	1000:1 Contrast
	400 NIT (typ.) Brightness
	Multi-touch projective capacitive touch
	Optical bonding for sunlight viewability
Memory	2GB LPDDR3
Processor	ARM® Cortex-A53 Octa-core 1.3 GHz
Storage	
Onboard	16GB eMMC
Expansion	SDHC-card (up to 32 GB)
RF Options	
Bluetooth	v 4.1
GNSS	GPS / AGPS / GLONASS
WLAN	802.11 a/b/g/n
WWAN North America	LTE Cat 4 / DC-HSPA+, b2/b4/b5/b13/b17 (ability to switch between operators)
WWAN Other regions	GSM/GPRS/EDGE, b2/b3/b5/b8 FDD-LTE / TDD-LTE, b1/b3/b4/b7/b8/b20/ b38/b39/b40/b41 WCDMA/HSDPA/HSPA, b1/b2/b4/b5/b8
Interfaces	
Audio	2x 1W Speaker
	1x Built-in Mic
Camera	Front: 2.0 MP webcam
	Rear: 8.0 MP auto focus w. LED flash
Data Capture	1D/2D barcode reader (optional)
	NFC reader
Indicators	1x LED (status)
Keys	1x Back
	1x Home
	1x Menu
	1x Power
	2x Volume keys
Ports	1x 19-pin docking connector
	1x Audio Combo connector (Mic in or Line Out)
	1x Micro SD Slot
	1x Micro USB 2.0 OTG
	1x Power Jack

Sensors	
Sensors	Digital compass
	G-sensor
	Light sensor
Power Supply	
Adapter	100-240V/ 12V DC 3A
Battery	7.4V, typ. 5140 mAh Li-Polymer Battery (2S1P)
	10 hours (depending on usage)
	Hot-swappable
Input	12 - 19 VDC
Security	
Lock	Kensington lock
Mobile Device Management	SOTI Mobicontrol compatible, available upon request
Operating System	
Android	Android
Physical Characteristics (with standard battery)	
Dimensions	271.67mm (w) x 198.2mm (h) x 21mm (d) 10.7 inch (w) x 7.8 inch (h) x 0.83 inch (d)
Weight	1.0 kg / 2.2 lb
Environment	
Drop	MIL-STD-810G (multiple 4-foot drop to concrete)
Dust and water	IP65
Humidity	30% to 90% RH, non-condensing
Operating temp.	-20°C to 60°C / 4°F to 158°F (AC mode)
	-10°C to 50°C / 14°F to 122°F (battery mode)
Salt Fog	MIL-STD-810G
Shock	MIL-STD-810G
Storage temp.	-20°C to 60°C / 4°F to 158°F
Vibration	MIL-STD-810G

JLT Mobile Computers

Head Office: Isbjörnsvägen 3, SE-352 45 Växjö, SWEDEN
Sales Office: Medborgarplatsen 3, Plan 8, SE-118 26 Stockholm, SWEDEN
Phone: +46 470 53 03 00 **Mail:** info@jltmobile.com

North America: 7402 West Detroit Street, Suite 150 Chandler, Arizona 85284, USA
Toll free US: 844-705-4200 **Intl Phone:** +1 480 705 4200 **Fax:** +1 480 397 1214 **Mail:** USsales@jltmobile.com
www.jltmobile.com

