



Nanjing Huade Storage Equipment Manufacturing Co., Ltd.
 No.90, Jia gang, Liang tang, Zhong hua men wai, Nanjing, P.R.C.
Step Beam Price List

Effected from Feb. 27th, 2008

Height	Depth	Loading Capacity	Step Tube								
				TYPE	SIZE						
h1	3" (76.2mm)	3.5" (88.9mm)	4" (101.6mm)	4" A (101.6mm)	4 1/2" (114.3mm)	5" (127mm)	5.5" (139.7mm)	6" (152.4mm)	6.25" (158.75mm)	6.25" A (158.75mm)	
Connector	3 rivets	3 rivets	3 rivets	3 rivets	3 rivets	3 rivets	3 rivets	4 rivets	4 rivets	4 rivets	
Thickness	1.5mm	1.5mm	1.75mm	1.5mm	1.7mm	1.7mm	1.7mm	1.9mm	1.9mm	2.1mm	
48"	7181	9200	10000	9200							
72"	3165	4693	8897	7094							
92"	1931	2864	5430	4330	6194	7860					
96"	1773	2628	5000	3973	5686	7215	9232				
100"	1633	2421	4591	3661	5238	6645	8504				
104"	1509	2237	4242	3383	4840	6141	7859				
108"	1398	2074	4000	3135	4600	5692	7285	10179	11288		
112"		1927	3655	2915	4169	5291	6770	9461	10493		
116"		1797	3406	2716	3886	4930	6309	8816	9778		
120"		1678	3182	2536	3629	4606	5894	8236	9134	10070	
124"			2979	2375	3398	4312	5518	7711	8550	9428	
128"			2795	2228	3188	4045	5177	7234	8022	8845	
136"			2474	1972	2823	3582	4583	6404	7102	7831	
140"			2334	1861	2662	3379	4324	6042	6700	7388	
144"			2206	1758	2516	3193	4086	5710	6332	6982	

Remarks:

1. All capacities are pair of beams based on uniformly distributed loads.
2. Deflection are limited to 1/180.